

DC EV Charger

JT40A



Wall standing

Floor standing


CE
UK
CA



BASIC



RFID



QR Code



POS

OEM Color & Pattern



Application Scenario



Highway



Parking Lot



Charging Station



Shopping Mall



Transport Company




IP54



OCPP



Ethernet/4G



7inch touch screens

Product Features

JT40-A

Charging equipment

Power	20KW/30KW/40KW/60KW
HMI	7 inch LCD color display touch screen
Installation method	Wall Mounted / Floor Standing
Wiring method	Bottom in and bottom out
Dimension	480*230*670mm
Weight	60-70KG
Input Voltage	AC400V±20%
Frequency	45~65Hz
Output Voltage	200~1000VDC
Max Output Current	0-150A
DC Plugs (Single/Double)	CCS1 / CCS2 / CHAdeMO / DC-GBT / Tesla
Communication Protocol	OCPP1.6J
Length of charging cable	5M(customizable)

Electrical indicators

Measuring accuracy	Level 0.5
Efficiency	≥95%
Power Factor	≥ 0.98
Harmonic content THD	≤5% (>50%Load)

Feature Design

Customization scope	Colors, Logos, Advertising Screens, Software
Charging mode	Automatic full charge / fixed power fixed amount / fixed time
Payment method	RFID/APP(QR Code)/Credit Cards(POS machine)
Communication Interface	Ethernet /4G -optional
Certificate	CE,UKCA

Environmental indicators

Working TEMP	-25°C~+50°C
IP Grade	IP54
Cooling method	Forced air cooling
Noise control	≤60dB